# WATER SOURCE HEAT PUMP UNIT SCHEDULE

| UNIT | TYPE | AIRFLOW CFM | FAN DATA EXTERNAL S.P. (IN. W.G.) | SENSIBLE CAPACITY (MBH) | TOTAL CAPACITY (MBH) | COIL DATA EAT (°F) DB | EAT (°F) WB | LAT (°F) DB | LAT (°F) WB | HEATING TOTAL CAPACITY | HEATING EAT.DB | HEATING NUM. OF STAGES | HEATING LAT.DB | CONDENSER DATA COOLING EWT (°F) | COOLING LWT (°F) | COOLING ΔP (FT. WG) | COOLING GPM | HEATING EWT | HEATING LWT | HEATING ΔP (FT. WG) | SINGLE POINT POWER CONNECTION MCA | MOCP | V | PH | SEER | C.O.P. | MANUFACTURER | MODEL NUMBER | WEIGHT | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| WSHP-1 | HORIZONTAL | 1760 | 0.66 | 43.4 | 57.0 | 75 | 63 | 52 | 51 | 55.0 | 72 | 1 | 101 | 90 | 101 | 6.10 | 13 | 50 | 43 | 7.80 | 16 | 20 | 480 | 3 | 14.8 | 4.3 | CLIMATE MASTER | SE-060 | 475.00 | ALL |
| WSHP-2 | HORIZONTAL | 1880 | 0.49 | 44.7 | 58.2 | 75 | 63 | 53 | 52 | 56.0 | 72 | 1 | 100 | 90 | 101 | 6.10 | 13 | 50 | 43 | 7.80 | 16 | 20 | 480 | 3 | 14.6 | 4.3 | CLIMATE MASTER | SE-060 | 475.00 | ALL |
| WSHP-3 | HORIZONTAL | 1100 | 0.34 | 42.4 | 35.1 | 75 | 63 | 55 | 51.7 | 36.7 | 72 | 1 | 103 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.3 | 4.7 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-4 | HORIZONTAL | 850 | 0.20 | 21.2 | 34.2 | 75 | 63 | 51.9 | 48.3 | 35.3 | 72 | 1 | 110 | 90 | 101 | 4.00 | 8 | 50 | 42 | 4.60 | 14 | 20 | 277 | 1 | 16 | 4.5 | CLIMATE MASTER | SE-024 | 360.00 | ALL |
| WSHP-5 | HORIZONTAL | 730 | 0.16 | 16.4 | 23.4 | 75 | 63 | 54 | 51.6 | 24.0 | 72 | 1 | 103 | 90 | 102 | 0.80 | 5 | 50 | 43 | 1.20 | 14 | 20 | 277 | 1 | 14 | 4.4 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-6 | HORIZONTAL | 870 | 0.56 | 21.2 | 34.1 | 75 | 63 | 51.9 | 48.3 | 35.3 | 72 | 1 | 110 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 16 | 4.5 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-7 | HORIZONTAL | 1480 | 0.23 | 36.0 | 49.0 | 80 | 66 | 58 | 55 | 60.0 | 68 | 1 | 105 | 86 | 98 | 4.40 | 10 | 68 | 58 | 4.50 | 16 | 20 | 480 | 3 | 15.6 | 5.1 | CLIMATE MASTER | SE-048 | 450.00 | ALL |
| WSHP-8 | HORIZONTAL | 1250 | 0.34 | 24.7 | 35.7 | 75 | 63 | 56.7 | 53 | 37.6 | 72 | 1 | 100 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 14.9 | 4.9 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-9 | HORIZONTAL | 1530 | 0.88 | 32.6 | 46.3 | 75 | 63 | 55 | 52 | 48.0 | 72 | 1 | 101 | 90 | 101 | 4.40 | 10 | 50 | 42 | 4.80 | 16 | 20 | 480 | 3 | 14.2 | 4.4 | CLIMATE MASTER | SE-048 | 450.00 | ALL |
| WSHP-10 | HORIZONTAL | 1545 | 0.13 | 32.7 | 46.3 | 75 | 63 | 55 | 52 | 48.0 | 72 | 1 | 101 | 90 | 101 | 4.40 | 10 | 50 | 42 | 4.80 | 16 | 20 | 480 | 3 | 14.2 | 4.4 | CLIMATE MASTER | SE-048 | 450.00 | ALL |
| WSHP-11 | HORIZONTAL | 4360 | 0.26 | 85.4 | 115.0 | 75 | 63 | 57 | 54 | 127.8 | 72 | 1 | 99 | 90 | 102 | 12.80 | 25 | 50 | 43 | 14.30 | 23 | 30 | 480 | 3 | 11.2 | 3.8 | CLIMATE MASTER | SE-120 | 700.00 | ALL |
| WSHP-12 | HORIZONTAL | 4450 | 0.22 | 86.0 | 115.0 | 75 | 63 | 57 | 54 | 128.0 | 72 | 1 | 99 | 90 | 102 | 12.80 | 25 | 50 | 43 | 14.30 | 23 | 30 | 480 | 3 | 11.2 | 3.8 | CLIMATE MASTER | SE-120 | 700.00 | ALL |
| WSHP-13A | HORIZONTAL | 3055 | 0.25 | 66.0 | 92.5 | 75 | 63 | 55 | 52 | 99.0 | 72 | 1 | 102 | 90 | 102 | 10.40 | 20 | 50 | 42 | 12.60 | 16 | 20 | 480 | 3 | 12.8 | 4.1 | CLIMATE MASTER | SE-096 | 645.00 | ALL |
| WSHP-13B | HORIZONTAL | 2100 | 0.25 | 46.8 | 59.0 | 75 | 63 | 54 | 53 | 57.8 | 72 | 1 | 98 | 90 | 102 | 6.10 | 13 | 50 | 43 | 7.80 | 16 | 20 | 480 | 3 | 14.3 | 4.4 | CLIMATE MASTER | SE-060 | 645.00 | ALL |
| WSHP-14 | HORIZONTAL | 1200 | 0.43 | 24.3 | 35.5 | 75 | 63 | 56.3 | 52.6 | 37.3 | 72 | 1 | 101 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.00 | 17 | 25 | 277 | 1 | 15 | 4.8 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-15 | HORIZONTAL | 3800 | 0.11 | 73.6 | 94.7 | 75 | 63 | 57 | 54 | 104.0 | 72 | 1 | 97 | 90 | 102 | 10.40 | 20 | 50 | 42 | 12.60 | 16 | 20 | 480 | 3 | 12.4 | 4.2 | CLIMATE MASTER | SE-096 | 645.00 | ALL |
| WSHP-16 | HORIZONTAL | 1975 | 0.38 | 45.7 | 58.5 | 75 | 63 | 53 | 52 | 57.0 | 72 | 1 | 100 | 90 | 102 | 6.10 | 13 | 50 | 43 | 7.80 | 16 | 20 | 480 | 3 | 14.5 | 4.4 | CLIMATE MASTER | SE-060 | 475.00 | ALL |
| WSHP-17 | HORIZONTAL | 1975 | 0.38 | 45.7 | 58.5 | 75 | 63 | 53 | 52 | 57.0 | 72 | 1 | 100 | 90 | 102 | 6.10 | 13 | 50 | 43 | 7.80 | 16 | 20 | 480 | 3 | 14.5 | 4.4 | CLIMATE MASTER | SE-060 | 475.00 | ALL |
| WSHP-18 | HORIZONTAL | 2100 | 0.28 | 51.4 | 68.4 | 75 | 63 | 52 | 51 | 64.0 | 72 | 1 | 100 | 90 | 101 | 8.70 | 15 | 50 | 44 | 10.80 | 16 | 20 | 480 | 3 | 13.3 | 3.7 | CLIMATE MASTER | SE-072 | 475.00 | ALL |
| WSHP-19 | HORIZONTAL | 2100 | 0.32 | 51.4 | 68.4 | 75 | 63 | 52 | 51 | 64.0 | 72 | 1 | 100 | 90 | 101 | 8.70 | 15 | 50 | 44 | 10.80 | 16 | 20 | 480 | 3 | 13.3 | 3.7 | CLIMATE MASTER | SE-072 | 475.00 | ALL |
| WSHP-20 | HORIZONTAL | 1190 | 0.44 | 24.2 | 35.5 | 75 | 63 | 56.2 | 52.5 | 37.2 | 72 | 1 | 101 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.1 | 4.8 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-21 | HORIZONTAL | 1215 | 0.41 | 24.4 | 35.6 | 75 | 63 | 56.4 | 52.7 | 37.4 | 72 | 1 | 101 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15 | 4.8 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-22 | HORIZONTAL | 850 | 0.54 | 21.2 | 34.2 | 75 | 63 | 51.9 | 48.3 | 35.3 | 72 | 1 | 110 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 16 | 4.5 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-23 | HORIZONTAL | 1100 | 0.34 | 23.4 | 35.1 | 75 | 63 | 55.3 | 51.7 | 36.7 | 72 | 1 | 103 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.3 | 4.7 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-24 | HORIZONTAL | 960 | 0.48 | 22.2 | 34.6 | 75 | 63 | 53.6 | 50 | 35.9 | 72 | 1 | 107 | 90 | 101 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.7 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-25 | HORIZONTAL | 2945 | 0.22 | 64.8 | 92.2 | 75 | 63 | 55 | 52 | 99.0 | 72 | 1 | 103 | 90 | 102 | 10.40 | 20 | 50 | 42 | 12.60 | 16 | 20 | 480 | 3 | 12.4 | 4.2 | CLIMATE MASTER | SE-096 | 645.00 | ALL |
| WSHP-27 | HORIZONTAL | 1490 | 0.21 | 32.2 | 46.1 | 75 | 63 | 55 | 52 | 48.0 | 72 | 1 | 102 | 90 | 101 | 4.40 | 10 | 50 | 42 | 4.80 | 16 | 20 | 480 | 3 | 14.3 | 4.3 | CLIMATE MASTER | SE-048 | 450.00 | ALL |
| WSHP-29 | HORIZONTAL | 1500 | 0.20 | 32.3 | 46.2 | 75 | 63 | 55 | 52 | 48.0 | 72 | 1 | 102 | 90 | 101 | 4.40 | 10 | 50 | 42 | 4.80 | 16 | 20 | 480 | 3 | 14.3 | 4.3 | CLIMATE MASTER | SE-048 | 450.00 | ALL |
| WSHP-30 | HORIZONTAL | 1250 | 0.32 | 24.7 | 35.7 | 75 | 63 | 56.7 | 53 | 37.6 | 72 | 1 | 100 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 14.9 | 4.9 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-31 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-32 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-33 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-34 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-35 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-36 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-37 | HORIZONTAL | 1250 | 0.32 | 24.7 | 35.7 | 75 | 63 | 56.7 | 53 | 37.6 | 72 | 1 | 100 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 14.9 | 4.9 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-39 | HORIZONTAL | 960 | 0.48 | 22.2 | 34.6 | 75 | 63 | 53.6 | 50 | 35.9 | 72 | 1 | 107 | 90 | 101 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.7 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-40 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 52.6 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-41 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 53 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-42 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 53 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-43 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-44 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.60 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-45 | HORIZONTAL | 900 | 0.54 | 21.6 | 34.4 | 75 | 63 | 52.7 | 49.1 | 35.5 | 72 | 1 | 109 | 90 | 101 | 4.00 | 8 | 50 | 43 | 4.00 | 16 | 25 | 277 | 1 | 15.8 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-46 | HORIZONTAL | 1250 | 0.32 | 24.7 | 35.7 | 75 | 63 | 56.7 | 53 | 37.6 | 72 | 1 | 100 | 90 | 102 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 14.9 | 4.9 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-48 | HORIZONTAL | 960 | 0.48 | 22.2 | 34.6 | 75 | 63 | 53.6 | 50 | 35.9 | 72 | 1 | 107 | 90 | 101 | 4.00 | 8 | 50 | 42 | 4.60 | 16 | 25 | 277 | 1 | 15.7 | 4.6 | CLIMATE MASTER | SE-036 | 360.00 | ALL |
| WSHP-49 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 53 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-50 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 53 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |
| WSHP-51 | HORIZONTAL | 800 | 0.30 | 17.1 | 23.7 | 75 | 63 | 55 | 53 | 24.0 | 72 | 1 | 100 | 90 | 102 | 0.80 | 5 | 50 | 42 | 1.20 | 14 | 20 | 277 | 1 | 13.8 | 4.5 | CLIMATE MASTER | SE-024 | 298.00 | ALL |

GENERAL NOTES:
1. PUMP IS TO HAVE A NON-OVERLOADING MOTOR.
2. MINIMUM RECOMMENDED CLEARANCE AROUND A PUMP IS 24 INCHES. MAINTAIN MINIMUM CLEARANCES AS REQUIRED FOR SERVICE, MAINTENANCE, AND INSPECTION.

REMARKS:
1. UNIT CAPACITIES ARE BASED ON THE ENTERING AIR AND WATER CONDITIONS IN SCHEDULE.
2. MC TO PROVIDE DISCONNECT. EC TO INSTALL DISCONNECT. COORDINATE WITH EC.
3. FIELD VERIFY UNIT ORIENTATION WITH EXISTING DUCTWORK TO MINIMIZED IMPACT TO DUCT CONNECTIONS.
4. PROVIDE WITH ECM MOTOR.
5. PROVIDE WITH MANUFACTURER'S THERMOSTAT AND BACNET CAPABILITY.

# PUMP

| TAG | SERVICE | TYPE | GPM | HEAD (FT.) | MOTOR HORSE POWER | MAX. RPM | CURRENT CHARAC. V | P | F | MANUFACTURER | MODEL NUMBER | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| P-3 | COOLING TOWER | VERTICAL INLINE | 750 | 35.00 | 20 | 1800 | 480 | 3 | 60 | GRUNDFOS | 60125-4P-20HP VLSE | 1-4,6 |
| P-4 | GEO HEAT EXCHANGER | VERTICAL INLINE | 750 | 35.00 | 20 | 1760 | 480 | 3 | 60 | GRUNDFOS | 60125-4P-20HP VLSE | 1-5 |

GENERAL NOTES:
1. PUMP IS TO HAVE A NON-OVERLOADING MOTOR.
2. MINIMUM RECOMMENDED CLEARANCE AROUND A PUMP IS 24 INCHES. MAINTAIN MINIMUM CLEARANCES AS REQUIRED FOR SERVICE, MAINTENANCE, AND INSPECTION.

REMARKS:
1. PROVIDE WITH VARIABLE FREQUENCY DRIVE.
2. DISCONNECT PROVIDED BY MC AS PART OF PUMP ASSEMBLY AND INSTALLED BY EC.
3. PROVIDE SHAFT GROUNDING RINGS.
4. PROVIDE CONTROLS COMPATIBLE WITH EXISTING BUILDING AUTOMATION SYSTEM.
5. 100% WATER.
6. 25% GLYCOL.

# CLOSED-CIRCUIT COOLING TOWER

| MARK | ENTERING WATER TEMP.(°F) | LEAVING WATER TEMP.(°F) | GPM | WATER PD (FT) | AMBIENT WET BULB TEMP. (°F) | GLYCOL TYPE | GLYCOL | FAN HP | CURRENT V | P | F | MANUFACTURER | MODEL | WEIGHT | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CT-1 | 98.0 | 88 | 300 | 12.4 | 78 | PROPYLENE | 25% | 15 | 460 | 3 | 60 | BAC | FXV-0806B-28D-L | 10314 | 1-4 |

REMARKS:
1. PROVIDE WITH VARIABLE FREQUENCY DRIVE.
2. STAINLESS STEEL CONSTRUCTION.
3. MOTOR SHALL BE OUT OF WATER STREAM.
4. PROVIDE WITH LADDERS AND PLATFORMS.

# PLATE AND FRAME HEAT EXCHANGER

| MARK | ACTUAL CAPACITY (BTU/HR) | COOLING TOWER (COLD) SIDE EWT(°F) | LWT(°F) | GPM | PRESSURE DROP (FT.) | GHEX (HOT) SIDE EWT(°F) | LWT(°F) | GPM | PRESSURE DROP (FT.) | MANUFACTURER | MODEL NUMBER | REMARKS |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| HX-1 | 3724827 | 85 | 95 | 774 | 17.3 | 100 | 90 | 750 | 13.2 | MUELLER | AT40MHV | 1-2 |

REMARKS:
1. EXCHANGER SHALL MEET OR EXCEED EFFICIENCIES AS OUTLINED IN ASHRAE 90.1.
2. COORDINATE EXACT LOCATION WITH MOORE PUBLIC SCHOOLS PRIOR TO INSTALLATION.


AGP
the Abla Griffin Partnership L.L.C.

313 S. E. 5th Street
MOORE, OK. 73160
405.735.3477
AGP@theAGP.net
www.theAGP.net


CEDAR CREEK
CIVIL

KFC ENGINEERING
STRUCTURAL

SALAS O'BRIEN
MECHANICAL / ELECTRICAL

STATE OF OKLAHOMA PROFESSIONAL ENGINEER
Dwayne Michael Gonzales
14308
04/29/26

KF
drawn by

DG
checked by

JANUARY 2026
date

REVISIONS

| Δ | DESCRIPTION | DATE |
|---|---|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

MOORE PUBLIC SCHOOLS

WAYLAND BONDS
2025 HVAC

sheet no:

M601


Salas O'Brien
Oklahoma City
2900 S. Telephone Road, Suite 120
Moore, OK 73160
CA#: 7058 Expiration Date: 06/30/2027
Salas O'Brien Project Number: 2550-01872-00



OWNERSHIP USE OF DOCUMENTS:

AGP EXPRESSLY RESERVES ITS COPYRIGHT AND OTHER PROPERTY RIGHTS OF ALL PLANS AND DRAWINGS DESIGNED AND/OR PRODUCED. PLANS AND DRAWINGS ARE NOT TO BE REPRODUCED IN ANY FORM OR MANNER WITHOUT THE EXPRESSED WRITTEN CONSENT OF AGP.